

# PICMG 1.3 Full-size CPU Card FS-A76

Support 3rd Generation Intel® Core™ i7/ i5/ i3/  
Pentium® Desktop Processor  
Onboard VGA, DVI, HD Audio  
Intel® Gigabit LAN , Serial ATA  
PCIE X16 , PCIE Minicard, PCI.TPM



<b>Form Factor</b>	PICMG 1.3 Full-size CPU Card
<b>CPU</b>	Supports 3rd Generation Intel® Core™ i7/ i5/ i3/ Pentium® Desktop Processor Package type: FCLGA1155
<b>Memory</b>	Two DDR3 1066/1333 DIMM up to 16 GB
<b>Chipset</b>	Intel® BD82Q77 PCH
<b>Real Time Clock</b>	Chipset integrated RTC with onboard lithium battery
<b>Watchdog Timer</b>	Generates a system reset with internal timer for 1min/s ~ 255min/s
<b>Power Management</b>	ACPI 3.0 compliant, supports power saving mode
<b>Serial ATA Interface</b>	Intel® Q77 PCH built-in 4 x Serial ATAII interface up to 300MB/s & 2 x Serial ATAIII interface up to 600MB/s Support RAID 0, 1, 5, 10 and Intel Rapid Storage Technology.
<b>VGA Interface</b>	Intel® Clear Video integrated HD Graphics Technology
<b>DVI Interface</b>	Onboard DVI with 20-pin connector
<b>Audio Interface</b>	Intel® integrated Q77 with Realtek ALC888 HD Audio.
<b>LAN Interface</b>	One Intel® 82574L Gigabit LAN & One Intel®82579LM Gigabit LAN support iAMT8.0
<b>GPIO interface</b>	Onboard programmable 8-bit Digital I/O interface.
<b>Extended Interface</b>	PICMG 1.3 Interface Support 1 PCI-Express x16 and 1 PCI-Express x4 or 4 PCI-Express x1 4 PCI bus master, and 4 USB2.0 Interface and 2 x PCIE mini card socket,
<b>Internal I/O Port</b>	1 x RS232/422/485, 1 x GPIO port, 1 x CDIN connector, 1 x Audio connector, 1 x IrDA, 1 x SIM socket, 1 x SMBUS connector, 5x Serial Port, 4 x USB 2.0, 4 x USB3.0, 1 x Parallel port.
<b>External I/O Port</b>	1 x PS/2 Keyboard/Mouse Port, 2 x RJ45 LAN ports, 1 x DB15 VGA port,
<b>Power Requirement</b>	+5V, +12 DC input & 5V <sub>SB</sub> Requirement
<b>Dimension</b>	338 mm x 126 mm (L x W)
<b>Temperature</b>	Operating within 0~60 centigrade Storage within -20~85 centigrade

HS Italia  
Tel. 0536 830620  
Fax. 0536 831215  
[www.hs-italia.it](http://www.hs-italia.it)  
[info@hs-italia.it](mailto:info@hs-italia.it)



**Ordering Code**

**FS-A76TDG** Onboard VGA, DVI, 4 x USB2.0, 4 x USB3.0, 6 x serial Port, 6 x SATA, 1 x IrDA, 1 x LPC  
Realtek HD 5.1CH Audio, GPIO and 2 x PCI Express mini card, **1 x Giga LAN (82579LM)**  
Support **Four X1 & One X16** PCI Express interface

**FS-A76FTDG** Onboard VGA, DVI, 4 x USB2.0, 4 x USB3.0, 6 x serial Port, 6 x SATA, 1 x IrDA, 1 x LPC  
Realtek HD 5.1CH Audio, GPIO and 2 x PCI Express mini card, **1 x Giga LAN (82579LM)**  
Support **One X4 & One X16** PCI Express interface

**FS-A76TDG2** Onboard VGA, DVI, 4 x USB2.0, 4 x USB3.0, 6 x serial Port, 6 x SATA, 1 x IrDA, 1 x LPC  
Realtek HD 5.1CH Audio, GPIO and 2 x PCI Express mini card, **2 x Giga LAN**  
Support **Four X1 & One X16** PCI Express interface

**FS-A76FTDG2** Onboard VGA, DVI, 4 x USB2.0, 4 x USB3.0, 6 x serial Port, 6 x SATA, 1 x IrDA, 1 x LPC  
Realtek HD 5.1CH Audio, GPIO and 2 x PCI Express mini card, **2 x Giga LAN**  
Support **One X4 & One X16** PCI Express interface

HS Italia  
Tel. 0536 830620  
Fax. 0536 831215  
[www.hs-italia.it](http://www.hs-italia.it)  
[info@hs-italia.it](mailto:info@hs-italia.it)

